

BUILDER PORTAL

WARRANTY

1.2 Drainage

Improper surface drainage.

Construction Performance Guidelines

Necessary grades and swales shall be established to provide proper drainage away from the Home. Site drainage, under the Limited Warranty, is limited to grades within 10-feet and swales within 20-feet of the foundation of the Home. Standing or ponding water shall not remain in these areas for a period longer than 24-hours after a rain, except in swales that drain from adjoining properties or where a sump pump discharges. In these areas an extended period of 48-hours is to be allowed for water to dissipate. The possibility of standing water after an unusually heavy rainfall should be anticipated and is not to be considered a deficiency. No grading determination is to be made while there is frost or snow or when the ground is saturated.

Builder/Seller/Warrantor Responsibility

Builder/Seller is only responsible for initially establishing the proper grades, swales and drainage away from Home. You are responsible for maintaining such grades and swales once constructed by the Builder/Seller. Builder/Seller is not responsible for drainage deficiencies attributable to grading requirements imposed by state, county, or local governing agencies.

Exclusion

Standing or ponding water outside of defined swales and beyond 10-feet from the foundation of the Home, or that is within 10-feet but is caused by unusual grade conditions, or retention of tree areas, is not considered a deficiency. Standing or ponding water caused by changes in the grade or placement of sod, fencing, or any other obstructions by You are excluded from Limited Warranty coverage.